

Scotsman° Ice Systems

Modular Ice Machine 290 k	(0)
---------------------------	-----

Item #:
Project:
Quantity:



FEATURES

- Hermetic compressor. Stainless steel auger and freezing cylinder (evaporator). Equipped with an electronic control board.
- Ice breaker made in specially strengthened alloy, allowing for greater extrusion pressure to deliver a dryer-quality of nugget ice (92% dry).
- Long-lasting stainless steel roller-bearings.
- Double protection electronic rotation sensor and drive coupling on gear motor and gear reducer.
- Low- water sensor protection on refrigeration and gear motor system. Optical ice level sensor for machine shut down.
- Stainless steel side panels in scotch-brite finish, with rounded corners for enhanced ease of cleaning and aesthetics.
- Side panels are removable on all four sides to ease maintenance and after-sales service operations.
- PS plastic top cover.

		CONDENSING	RECOMMENDED BINS				
		SYSTEM	Head	Bins		kg	
		A: 1 1		CBT22EFCD	SB193	129	
	MFN S 47 Nugget Small 1 g	Air cooled	MFN 47	CBT22EFCD	SB322	168	
	Ø 11 x H 13 mm			CBT30EFSD	SB393	181	
	MENIN 47	REFRIGERANT		CBT30EFSD	SB530	243	
		GAS		CBT42EFSD	SB550	252	
				CBT48FMCD	SB948	406	
	MFN M 47 Nugget Medium 4 g	R290		CBT52FMCD	SB1025	478	
	Ø 17 x H 15 mm			•	UBH1100	553	
		VOLTAGE		•	SIS300	137 + 73	
		V/Hz/ph		•	SIS700	318 + 73	
		230/50/1	LEGEND: ✓: Perfect combination between ice maker and bin o: Ice chute cut-out performed upon installation CBTxxxxxxxxxx : need additional bin top				

RTIFICATIONS



Minimum Maximum Air temperature 10 43 Water temperature 5 38 Water pressure 1 bar (14 psi) 5 bar (70 psi) Electrical voltage -10% +10%

OPERATING REQUIREMENTS

IMPORTANT NOTICE

lels and specifications a ge without notice.
spec sheet is meant for consortection ose only.
For technical documentation please refer to our service manuals.

Download our free **App Scotsman Ice**Apple store
Google play
Windows store

www.scotsman-ice.it www.scotsman-ice.com


Size (W x D x H)

MFN 47 Eco



Modular Ice Machine 290 kg

Item #:
Project:
Quantity:



Net weight /8 kg				Weight 8/kg							
		24 h ice production kg °C Amb. / °C Water		Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size	
Version	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/	kWh/	l/h	W	w	No. x Ømm²	А
		kg	kg	kg	100 kg	24h					
MFN S47 AS	230/50/1	290	270	215	10.6	22.9	8.5	950	840	3 x 1.0	10
MFN M47 AS	230/50/1	270	240	208	10.6	22	9.1	1000	840	3 x 1.0	10

610 x 760 x 820 mm

Carton (W x D x H)

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions

538 x 663 x 645 mm